DUNE
UNIQUE MATTERS

TECHNICAL GUIDE

Installation guide for mosaics of other materials

Recommendations for installing, grouting and maintaining mosaics of other materials.

01 Surface preparation

Before tiling, the substrate must be firm, clean and perfectly level.

If the substrate is uneven, correct it with suitable levelling products. **Never level using the adhesive.** Also repair any cracks or imperfections until the wall is completely smooth.

> 2 mm
Unevenness above which the substrate must be **levelled** with suitable products.

< 2 %
Maximum permissible moisture in the **wall** before tiling.

02 Adhesive material

The choice of adhesive depends on several factors that should be assessed before starting.

- The substrate material to be covered (plasterboard, synthetic panels, plaster, wood…).
- The stability of the substrate.
- The area to be covered.
- The ambient conditions.
- The speed at which the work is to be carried out.

The adhesives recommended by DUNE have been tested at our facilities, under controlled ambient conditions and on rigid brick or concrete substrates. For any other type of installation, carry out a test first and, if in doubt, consult DUNE or the adhesive manufacturer directly.

ALWAYS CARRY OUT A TEST

Before installing all the material, test the system on at least **2 pieces**. Also check that the chosen adhesive is suitable for the material to be installed.

Adhesive by mosaic composition

Mosaic composition	Recommended adhesive
Glass and stone	C2 tile adhesive
Glass and metal	C2 tile adhesive or epoxy adhesive
Stone and metal	C2 tile adhesive
With resin components	C2 tile adhesive

See the references in the adhesives table in section 06.





03 Installation

Fresh adhesive and full coverage of the tile are the key to a long-lasting installation.

1 **Start at the bottom**

- Work from the bottom upwards, allowing the lower rows to dry.

2 **Spread the adhesive**

- Apply a thin layer (approx. 3 mm) on the area where the piece will go.
- Comb it with a no. 3 notched trowel to form the ridges.

3 **Lay the piece**

- Do so while the adhesive is still soft and before a dry skin forms on the surface.
- Press gently to achieve good adhesion and remove any voids without adhesive.

4 **Keep joints even**

- Make sure the gap between sheets equals the joint between the tesserae.

5 **Take care where sheets meet**

- On irregular mosaics, remove and reposition some tesserae where two meshes meet to improve the finish.

MESHES WITH STONE COMPONENTS

Before installation, treat these meshes with sealer. DUNE recommends and distributes the **stain-proof sealer** and/or the **protective liquid wax**.

MODELS WITH RESIN COMPONENTS

NEREIDA, HERMES, POSEIDON, NAYADE and KARAT must not be installed near heat sources such as radiators, saunas or hobs.

JOY AND SMILE MODELS

These require careful handling to avoid breaking their stone components.

04 Grouting

The final finish depends on both the material and cleanliness during application.

1 **Prepare the joints**

- They must be clean and dry, with a minimum depth of 2 mm.

2 **Apply the grout**

- Spread it with a smooth trowel, filling all the joints.

3 **Clean immediately**

- Do not let excess material dry: remove it as soon as possible with a damp sponge and neutral pH cleaning products.
- Never use abrasive products.
- If the material has dried, use cement or epoxy grout residue removers (the latter **are not suitable for stone**).

For greater water resistance, **epoxy grout** is recommended, especially in wet areas, but **never on stone mosaics**. See the grout table in section 06.

CHOOSE THE COLOUR CAREFULLY

The grout colour affects the final appearance. DUNE advises a test before grouting the whole surface.

SCRATCH-SENSITIVE MODELS

With metal components: PLANETARIUM, STATUS, THOR, KRAKATOA, LENS, GLOBE, MAGMA GREY, MAGMA COPPER, ARCADIA, CASABLANCA, NIAGARA, AQUARIUS, PLEYADES, CASSIOPEIA and ESMERALDA.

With resin components: POSEIDON, NAYADE, HERMES and NEREIDA.

All of these have low scratch resistance. For a good finish, use a fine-grain grout and clean off the excess with a sponge and plenty of clean water, without pressing too hard: this is when most scratches occur. Always carry out a grouting test on one piece before continuing.



05 Cleaning and maintenance

Daily maintenance is simple if the right products are used.

Routine cleaning can be done with standard neutral pH products, without abrasive cleaning materials.



06 Recommended products

References for adhesives, treatment products and grouts.

Adhesives

Manufacturer	C1 tile adhesive	C2 tile adhesive	Epoxy adhesive
KERAKOLL	ESPECIAL ECO	H 40 ECO FLEX	SUPERFLEX ECO
MAPEI	TIXOBOND	KERAFLEX MAXI S-1	KERALASTIC T

Manufacturer	Latex adhesive mortar
LATICRETE	Mortar 211 + Laticrete 4237

Treatment products

Surface	Code	Description	PHP code
GLASS	185463	ANTIGLISS	D787
STONE	184507	LIQUID PROTECTIVE WAX	D945
STONE	184508	STAIN-PROOF SEALER	D969

Grouts

Manufacturer	Cementitious grout	Epoxy grout
KERAKOLL	FUGABELLA ECO PORCELANA	FUGALITE
MAPEI	KERACOLOR FF	KERAPOXY
LATICRETE	LATICRETE 1600 series	—

DUNE

UNIQUE MATTERS

HEAD OFFICE

Partida Rachina, 12130 - Sant Joan de Moró (Castellón) - España

CONTACT

+34 964 657 400

dune@duneceramics.com

www.duneceramics.com